



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
-----------------	-------------	----------------------	---------------------	------------------

10/660,834

09/12/2003

John W. Carter

GEN10 P444

7859

28469

7590

11/15/2005

PRICE, HENEVELD, COOPER, DEWITT, & LITTON,
LLP/GENTEX CORPORATION
695 KENMOOR, S.E.
P O BOX 2567
GRAND RAPIDS, MI 49501

EXAMINER

THOMAS, BRANDI N

ART UNIT

PAPER NUMBER

2873

DATE MAILED: 11/15/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary

Application No.

10/660,834

Applicant(s)

CARTER ET AL.

Examiner

Brandi N. Thomas

Art Unit

2873

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 07 September 2005.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-52 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☒ Claim(s) 34-52 is/are allowed.
- 6) ☒ Claim(s) 1-33 is/are rejected.
- 7) ☒ Claim(s) 14 is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 12 September 2003 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. _____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
- * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- 1) ☒ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- 3) ☐ Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
Paper No(s)/Mail Date _____
- 4) ☐ Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____
- 5) ☐ Notice of Informal Patent Application (PTO-152)
- 6) ☒ Other: Detailed Action.

DETAILED ACTION

Claim Rejections - 35 USC § 102

1. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

2. Claims 1-33 are rejected under 35 U.S.C. 102(e) as being anticipated by Pastrick et al. (6276821 B1).

Regarding claims 1 and 12, Pastrick et al. discloses, in figures 1-5, a rearview mirror assembly for a vehicle comprising: a housing (34) configured for attachment to the vehicle (col. 6, lines 56-59); a mirror (28) positioned in said housing (34) (col. 7, lines 4-8); a turn signal light source (32a) (col. 8, line 66 and col. 9, line 1); and a door illuminator light source (30) configured to project light towards the door handle and/or locking mechanism (88) of the vehicle (col. 6, lines 54-55 and col. 8, lines 27-52).

Regarding claim 2, Pastrick et al. discloses, in figures 1-5, a rearview mirror assembly for a vehicle, wherein said mirror (28) is an electrochromic mirror (col. 7, lines 24-25).

Regarding claim 3, Pastrick et al. discloses, in figures 21-23, a rearview mirror assembly for a vehicle, wherein said light sources (230 and 232) comprise at least one LED device (col. 13, lines 62-66).

Regarding claim 4, Pastrick et al. discloses, in figures 1-5, a rearview mirror assembly for a vehicle, and further comprising a blind spot indicator light source (216) for indicating when an object is detected in a blind spot of the vehicle (col. 9, lines 52-55).

Regarding claim 5, Pastrick et al. discloses, in figures 1-5, s rearview mirror assembly for a vehicle, wherein said door illuminator light source (30) is further configured to function as a blind spot indicator light source (216) for indicating when an object is detected in a blind spot of the vehicle (col. 9, lines 52-60).

Regarding claim 6, Pastrick et al. discloses, in figure 43, s rearview mirror assembly for a vehicle, wherein at least one of said light sources (818) is disposed behind said mirror (816) so as to project light through said mirror (816) (col. 27, lines 4-6).

Regarding claim 7, Pastrick et al. discloses, in figures 1-5, s rearview mirror assembly for a vehicle, wherein said turn signal light source (32) and said door illuminator light source (30) are mounted in a common lamp module (figure 1).

Regarding claim 8, Pastrick et al. discloses, in figures 1-5, s rearview mirror assembly for a vehicle, wherein said door illuminator light source (30) is activated during both a door illumination lighting mode and a turn signal lighting mode (col. 7, lines 39-44).

Regarding claim 9, Pastrick et al. discloses, in figures 1-5, s rearview mirror assembly for a vehicle, wherein said turn signal light source (32) and said door illuminator light source (30) are coupled to a control circuit (74) for receiving activation signals therefrom (col. 8, lines 6-9 and 40-52).

Regarding claim 10, Pastrick et al. discloses, in figures 1-5, s rearview mirror assembly for a vehicle, further comprising a second door illuminator light source (32b) coupled to the control circuit (74), wherein the control circuit (74) sequentially activates said door illuminator light sources (32b) and said turn signal light source (32a) during a turn signal lighting mode (col. 7, lines 39-44).

Regarding claim 11, Pastrick et al. discloses, in figures 1-5, s rearview mirror assembly for a vehicle, wherein said door illuminator light source (30) is disposed behind said mirror so as to project light through said mirror (figure 1).

Regarding claim 13, Pastrick et al. discloses, in figures 21-23, a light module for a vehicle rearview mirror assembly, wherein said turn signal light source (230) and said door illuminator light source (232) comprise at least one LED device (col. 13, lines 62-66).

Regarding claim 15, Pastrick et al. discloses, in figures 21-23, a light module for a vehicle rearview mirror assembly, wherein said door illuminator light source (30) emits effective white light (col.7, lines 41-44) and said turn signal light source (32) emits light of a color selected the group consisting of: amber, red, orange, and red-orange (col. 8, line 67 and col. 9, line 1).

Regarding claim 16, Pastrick et al. discloses, in figures 21-23, a light module for a vehicle rearview mirror assembly, said light module comprising: a blind spot indicator (216) for indicating when an object is detected in a blind spot of the vehicle (col. 9, lines 52-55); and a door illuminator (30) configured to project light at a portion of a door of the vehicle (col. 6, lines 54-55 and col. 8, lines 27-52).

Regarding claim 17, Pastrick et al. discloses, in figures 21-23, a light module for a vehicle rearview mirror assembly, wherein said light module includes at least one LED device that is selectively actuated to function as both said blind spot indicator (216) and said door illuminator (30) (col. 13, lines 62-66).

Regarding claim 18, Pastrick et al. discloses, in figures 21-23, a light module for a vehicle rearview mirror assembly, further including a deviator for redirecting a portion of the light emitted from said at least one LED device towards the eyes of a driver of the vehicle for blind spot indication (col. 7, lines 55-67 and col. 8, lines 1-5).

Regarding claim 19, Pastrick et al. discloses, in figures 21-23, a light module for a vehicle rearview mirror assembly, further comprising a reflector disposed relative to said at least one LED device to direct light emitted from said at least one LED device in a desired direction, said deviator being a facet in said reflector (col. 14, lines 39-43).

Regarding claim 20, Pastrick et al. discloses, in figures 21-23, a light module for a vehicle rearview mirror assembly, wherein said at least one LED device emits effective white light when operating in a door illumination mode and emits light of a different color when operating in a blind spot indicator mode (col. 7, lines 41-44 and col. 8, line 67 and col. 9, line 1).

Regarding claim 21, Pastrick et al. discloses, in figures 21-23, a light module for a vehicle rearview mirror assembly, further including a turn signal light (32) (col. 8, lines 66-67 and col. 9, line 1).

Regarding claim 22, Pastrick et al. discloses, in figures 1-5, a rearview mirror assembly for a vehicle comprising: a housing (34) configured for attachment to the vehicle (col. 6, lines 56-59); a mirror (28) positioned in said housing (34) (col. 7, lines 4-8); a turn signal light source

Art Unit: 2873

(32a) (col. 8, line 66 and col. 9, line 1); and a door illuminator light source (30) configured to project light towards the door handle and/or locking mechanism (88) of the vehicle (col. 6, lines 54-55 and col. 8, lines 27-52); and a blind spot indicator light source (216) for indicating when an object is detected in a blind spot of the vehicle (col. 9, lines 52-55).

Regarding claim 23, Pastrick et al. discloses, in figures 21-23, a rearview mirror assembly for a vehicle, wherein said light sources (230 and 232) comprise at least one LED device (col. 13, lines 62-66).

Regarding claim 23, Pastrick et al. discloses, in figures 21-23, a rearview mirror assembly for a vehicle, wherein said door illuminator light includes at least one LED device for emitting effective white light (col. 13, lines 57-64).

Regarding claim 24, Pastrick et al. discloses, in figures 21-23, a rearview mirror assembly for a vehicle, wherein said at least one LED device includes a plurality of differently colored LED chips, and wherein at least one of said LED chips is selectively energized to function as said blind spot indicator light (col. 13, lines 57-67 and col. 14, lines 1-25).

Regarding claim 25, Pastrick et al. discloses, in figures 21-23, a rearview mirror assembly for a vehicle, wherein said at least one LED device includes an LED chip that emits red light when activated to provide a warning of an object in the vehicle's blind spot (col. 13, lines 57-67 and col. 14, lines 1-25).

Regarding claim 26, Pastrick et al. discloses, in figures 21-23, a rearview mirror assembly for a vehicle, wherein said at least one LED device includes a first LED chip that emits amber light when activated to provide an indication that blind spot detection system to which the LED device is coupled is operational (col. 13, lines 57-67 and col. 14, lines 1-25).

Art Unit: 2873

Regarding claim 27, Pastrick et al. discloses, in figures 21-23, a rearview mirror assembly for a vehicle, wherein said at least one LED device further includes a second LED chip that emits blue-green light, when said first and second LED chips are simultaneously activated the LED chips emit light that mixes and forms effective white light illumination that is projected towards a door handle of the vehicle (col. 13, lines 57-67 and col. 14, lines 1-25).

Regarding claim 28, Pastrick et al. discloses, in figures 21-23, a rearview mirror assembly for a vehicle, wherein said at least one LED device includes a first LED chip that emits blue-green light when activated to provide an indication that blind spot detection system to which the LED device is coupled is operational (col. 13, lines 57-67 and col. 14, lines 1-25).

Regarding claim 29, Pastrick et al. discloses, in figures 1-5, s rearview mirror assembly for a vehicle, wherein said turn signal light source (32) and said door illuminator light source (30) are mounted in a common lamp module (figure 1).

Regarding claims 30 and 31, Pastrick et al. discloses, in figure 43, s rearview mirror assembly for a vehicle, wherein at least one of said light sources (818) is disposed behind said mirror (816) so as to project light through said mirror (816) (col. 27, lines 4-6).

Regarding claim 32, Pastrick et al. discloses, in figures 21-23, a light module for a vehicle rearview mirror assembly, said light module comprising: a blind spot indicator (216) for indicating when an object is detected in a blind spot of the vehicle (col. 9, lines 52-55); and a turn signal light source (32a) (col. 8, line 66 and col. 9, line 1).

Regarding claim 33, Pastrick et al. discloses, in figures 21-23, a light module for a vehicle rearview mirror assembly, further comprising a reflector disposed to direct light emitted

Art Unit: 2873

from said turn signal light and said blind spot indicator in a desired direction (col. 14, lines 39-43).

Allowable Subject Matter

3. Claims 34-52 are allowed.
4. Claim 14 is objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.
5. The prior art taken either singularly or in combination fails to anticipate or fairly suggest the limitations of the independent claim(s), in such a manner that a rejection under 35 U.S.C. 102 or 103 would be proper. The prior art fails to teach a combination of all the claimed features as presented in claim(s) 14 and 34-37, wherein the claimed invention comprises a reflector having at least two reflector cups, wherein each LED device is associated with one of the reflector cups; and a turn signal indicator comprising a first, second, and third light source that are sequentially activated, as claimed.

Response to Arguments

6. Applicant's arguments with respect to claims 1-52 have been considered but are moot in view of the new ground(s) of rejection.

Art Unit: 2873

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Brandi N. Thomas whose telephone number is 571-272-2341. The examiner can normally be reached on 7- 4:30.



If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Ricky Mack can be reached on 571-272-2333. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).



BNT

November 7, 2005



RICKY L. MACK
PRIMARY EXAMINER